

Universal Ultra AR-AFFF Foam



Highest Class B Foam fire ratings in the industry

Badger's unique line of portable foam fire extinguishers contain an alcohol resistant (AR) type of aqueous film-forming foam (AFFF). They are specifically formulated for optimum performance in a hand portable fire extinguisher. This means when sufficiently applied, *Universal Ultra's* vapor sealing capability can actually prevent a fire from happening.

Badger foam units are effective on Class A common combustibles as well as hydrocarbon and polar solvent types of Class B flammable liquids, so they eliminate the application guesswork often associated with other foams. The unique synthetic base of *Universal Ultra* foam has no offensive odor, is non-toxic, environmentally-friendly, biodegradable and extremely simple to use and clean up.

Features:

- *Plated brass valves with stainless steel handle and lever*
- *Large, easy-to-pull stainless steel ring pin*
- *Heavy-duty machined and anodized aluminum air aspirating nozzle*
- *Suppresses flammable liquid vapors to prevent re-ignition*
- *UL Listed*
- *Six year warranty*
- *AR-AFFF Foam works on both hydrocarbon and polar solvent types of liquid fuels*
- *Full stainless steel cylinder and base*
- *Hex valve collar tightening ring for easy recharge*



Datos técnicos:

Espuma ultra universal AR-AFFF *Portátiles BADGER con extra presión almacenada*

MODEL	F-250
NUMERO DE PARTE	23697
CAPACIDAD (galon)	2.5
CAPACIDAD (litro)	9.46
CLASIFICACION DE INCENDIOS UL	1-A:30-B
TIPO DE AGENTE	AR-AFFF Foam
MATERIAL DEL CILINDRO	Acero inoxidable
MATERIAL DEL A VALVULA	Plated Brass
MATERIAL DEL ASA/PALANCA	Acero inoxidable
PROPULSOR	Nitrogeno/Aire
PRESION DE OPERACION @ 70° F	100
RANGO DE TEMPERATURA (° F)	35 to 120
RANGO DE TEMPERATURA (° C)	1.7 to 48.9
TASA DE FLUJO DEL AGENTE (lb/sec)	0.27
TASA DE FLUJO DEL AGENTE (kg/sec)	0.12
TIEMPO NOMINAL DE DESCARGA (sec)	90 to 110
RANGO DE DESCARGA (PIES)	10.0 to 15.0
RANGO DE DESCARGA (M)	3 to 4.6
ALTURA DE LA UNIDAD (PULG.)	24.5
ALTURA DE UNIDAD (CM)	62.2
ANCHO DE UNIDAD (PULG.)	8.75
ANCHO DE UNIDAD (CM)	22.2
PROFUNDIDAD DE UNIDAD (PULG.)	7
PROFUNDIDAD DE UNIDAD (CM)	17.8
PESO DE ENVIO (LB)	12
PESO DE ENVIO (KG)	5.4
APROBACIÓN DE USCG	n/a
SOPORTE	UB-20 Opcional

Esta información está sujeta a cambios sin previo aviso. Badger Fire Protection se exime de cualquier responsabilidad por cualquier error o mala interpretación de la información contenida en él. Contacte a Badger Fire Protection de su distribuidor local para obtener ayuda.

Distribuido por:

Badger Fire Protection
944 Glenwood Station Lane, Suite 303
Charlottesville, VA 22901
Tel.: 434.964.3200 • Fax: 434.964.3202
www.badgerfire.com May 2013

SS B-011
All Rights Reserved.

May 2013

